



2.22 Declaration of Performance Woodsafe WFX Sweet chestnut panel

| | | | |
|--|---|---|----------------------------------|
| <i>Document name</i> 2.22 Declaration of Performance Woodsafe WFX Sweet chestnut panel | <i>Governing document</i> CPR305/2011, EN14915:2013 0402-CPR-SC0260-15 | <i>Language / Språk</i> English | <i>Number of pages DoP</i> 3 |
| <i>Fire impregnation system</i> WOODSAFE® Exterior WFX™ | <i>Description</i> Waterproof (polymeric) fire impregnation for wooden panels | <i>Version</i> 1 | <i>Product code</i> 22 |
| <i>Compiled by</i> Peter Johnson, CPO peter.johnson@woodsafes.com | | <i>Supersedes edition</i> | |
| <i>Approved by</i> Thomas Bengtsson, CEO thomas.bengtsson@woodsafes.com. | | <i>Date</i> 2023-04-04 | |

1. Product group

WOODSAFE® WFX Sweet chestnut panel, in thickness min 22mm.

2. Construction product identification

Fire protection system: WOODSAFE® Exterior WFX, fire impregnation
Wood treatment: -
Wood specie and product type: Sweet chestnut panel
Surface treatment: -
Product code: 22

Sawn, planed and profiled wooden panels with or without tongue and groove that meet the requirements according to EN14915:2013. Fire protection impregnated according to system Woodsafe Exterior WFX. For more information, see page 2 of this Declaration of performance as well as package specification and associated document.

3. The products intended end use/uses

Exterior wooden panel as cladding with material properties against fire.

4. Manufacturer

Business: Woodsafe Timber Protection AB with place of manufacture, Fågelbacken brandövningsplats, 72595 Västerås, Sverige.
VAT: SE556630532101
Phone: 010-206 72 30. Technical support 010-206 72 37.
E-mail: kundtjanst@woodsafes.com
Website: www.woodsafes.com
Registered trademark: WOODSAFE® Exterior WFX™

5. System for assessment and continuous control of the construction product's performance, system 1

System 1 for reaction to fire and system 4 for other properties. Production is carried out, controlled and operated by the quality system WQS (Woodsafe Quality System). The quality system ensures that the performance of the manufactured products complies with the characteristics declared in this performance declaration.

6. Declared performance in accordance with harmonized standard and notified body

Fire classification

- EN13501-1


Harmonized product standard wood panels

- EN14915:2013

Control body for continuous manufacturing control

- RISE No.0402 Control agreement number 210-09-0082, Rev. 2014-12-11.
- Control of continuity of product performance according to system 1 and has issued attestation of continuity of product performance.

7. Stated performance

| Essential properties | Performance | | | |
|---------------------------|---------------------------|--|-----------------------|----------------------|
| Reaction to fire | Fire class | B-s1,d0 at 22mm thickness. B-s2,d0 at >22mm thickness Classified according to EN13501-1 | | |
| | Joints | Horizontal and vertical | | |
| | Installation (1,2,3,4) | 1 – Assembly: Horizontal – OK Vertical - Mechanically attached 2 – With or without an air gap to the substrate 3 – Wood based substrates Euroclass D-s2,d0 or better <i>alternatively</i> all substrates with Euroclass A1 or A2s1,d0 with minimum thickness 8mm and density min 338 kg/m ³ . 4 – NPD | | |
| | | Horizontal installation | Vertical installation | |
| | |  | | |
| | Battens | Wooden battens 38mm thickness (<i>not fireproof impregnated</i>) | | |
| | Substrate (3) | Density | Minimum thickness | Fire class EN13501-1 |
| | Min 338 kg/m ³ | 8mm | A1, d0 or A2s1, d0 | D-s2,d0 |
| Release of formaldehyde | NPD | | | |
| Pentachlorophenol content | None | | | |
| Vapor permeability | NPD | | | |
| Sound absorption | NPD | | | |

| Use class | Area of use | | | Additional information |
|-----------|------------------------------------|---------------------------------------|--|--|
| EN16755 | INT1 <i>Normal dry interior</i> | INT2 <i>Varying moist interior</i> | EXT <i>Damp interior and exterior environment</i> | The fire retardant is approved for exterior exposure without surface treatment requirements. Can also be used in an interior environment. Approval is confirmed in a separate type approval certificate. |

| | |
|--------------|---|
| Intended use | Exterior |
| Panel type | Fire protection impregnated cladding |
| Wood specie | Sweet chestnut (<i>Castanea Sativa</i>) |
| Density | 514-775 kg/m ³ |
| Fastening | Stainless steel screw or nail (A2-A4) |



2.22 Declaration of Performance Woodsafe WFX Sweet chestnut panel

8. REACH: SVHC (Substances of Very High Concern)

WOODSAFE® Exterior WFX consistent with both REACH Regulation (EC) 1907/2006 and the Biocidal Products Regulation (EU) 528/2012. Exterior WFX does not contain any prohibited chemicals according to REACH. Some substances may be on the SVHC list according to CLP regulations, but as a final product and using fire retardant treated wood, Woodsafe Exterior WFX is not classified as hazardous to health or the environment.

9. Related documents

Recommendation, guidance for use and maintenance of the product is available at www.woodsafes.com document library.

Västerås 2023-04-04

Woodsafe Timber Protection AB

Thomas Bengtsson, CEO

WOODSAFE®